(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 8 April 2004 (08.04.2004)

PCT

(10) International Publication Number WO 2004/030238 A1

(51) International Patent Classification7: H04Q 7/22

H04B 7/06.

(21) International Application Number:

PCT/IB2003/003985

(22) International Filing Date:

12 September 2003 (12.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0222555.5

28 September 2002 (28.09.2002)


- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MOULSLEY, Timothy, J. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).

BAKER, Matthew, P., J. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB). CAMERON, Alistair, S. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).

- (74) Agent: WHITE, Andrew, G.; Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: PACKET DATA TRANSMISSION IN A MIMO SYSTEM



(57) Abstract: A packet data transmission system comprises primary stations (PS) having signal transmitting and receiving means and antennas (PA1 to PA4) for propagating downlink signals and receiving uplink signals and a plurality of secondary stations (SS) able to roam within the coverage areas of the primary stations. Each secondary station (SS1) has signal transmitting and receiving means, a predetermined number of antennas (SA1 to SA4), and means for monitoring its radio environment. Information about the radio environment is relayed as an uplink signal to the respective primary station which modifies its mode of transmission of packet data signals. The secondary station in response to the modified mode of transmission of the downlink signals adapts its receiver resources to process the packet data signals and effect cancellation of any interference.

